



COEPOX 201 (0.5~1.5mm)

环氧多用途自流平系统 MULTI-FUNCTION EPOXY SELF-LEVELLING SYSTEM

COEPOX 201 (0.5~1.5mm) 是一种双组份或三组份的, 多用途环氧自流平地坪系统。可用作底涂, 亦可搭配色浆施工为彩色面涂, 使用单一产品即可施工成完整的环氧地坪系统。

COEPOX 201 (0.5~1.5mm) is a two-component or three-component, multi-function epoxy self-levelling flooring system. It can be used as a primer or as a colored topcoat (paired with color paste). A complete epoxy flooring system can be constructed using this single product.

适用场所 Applications

- > 食品及食品加工行业
Food and food processing industry
- > 超市、购物中心
Supermarkets, shopping centers
- > 医院 Hospitals
- > 实验室 Laboratories
- > 无菌区域 Aseptic area
- > 制药工业 Pharmaceutical industry
- > 化学工业 Chemical industry
- > 行车频繁区域如汽修厂及汽车库
Garages and vehicle depots subjected to medium-to-heavy traffic
- > 食堂 Canteens
- > 轻工业 Light engineering industry
- > 展会、交易会 Exhibition and trade fair halls
- > 贮藏库 Storage depots

无溶剂, 无毒无味
Solvent-free, non-toxic and odorless

良好的耐磨及耐化学品性能
Good wear and chemical resistance

洁净度佳
Good cleanliness

装饰性强
Strong decorative properties

多用途、易施工
Multi-function, easy to apply

技术标准 Technical standard					
固体含量 Solid content		100%			
混合物比重 Density of mixture		~1.48g/cm ³			
混合物粘度 Viscosity of mixture		~2460MPa·s			
邵氏硬度 (D型) Shore hardness (Type D)		~84			
步骤 Step	产品 Product	说明 Information	理论用量 Consumption	施工方法 Application method	覆涂间隔时间 Overcoating
基面 Substrate	处理 Preparation	机械处理, 清洁 Mechanical treatment and cleaning of substrate			
底涂 Primer	COEPOX 201	多用途环氧自流平 Multi-function epoxy self-levelling coating	0.3~0.5kg/m ²	滚涂 / 刮涂 Roller / Scraper	24小时后 Allow 24 hours
薄涂面层 Thin coated finish	COEPOX 201	多用途环氧自流平 Multi-function epoxy self-levelling coating	0.25~0.3kg/m ² · 道, 建议施工2道 0.25~0.3kg/m ² · layer, 2 layers is suggested	滚涂 Roller	
基面 Substrate	处理 Preparation	机械处理, 清洁 Mechanical treatment and cleaning of substrate			
底涂 Primer	COEPOX 201	多用途环氧自流平 Multi-function epoxy self-levelling coating	0.3~0.5kg/m ²	滚涂 / 刮涂 Roller / Scraper	24小时后 Allow 24 hours
自流平面层 Self-levelling finish	COEPOX 201 + QUARTZ 0.25	多用途环氧自流平面涂 + 0.25mm的石英砂 Multi-function epoxy self-levelling coating with 0.25mm quartz sand	1.3~1.5kg/m ²	镘涂+滚筒消泡 Trowel+Roller	

